TRANSMISSION OK

TX/RX NO RECIPIENT ADDRESS DESTINATION ID

ST. TIME TIME USE PAGES SENT RESULT 0255

6797#3994994#149832#15712731436#

06/23 11:49 00'39

or

porterwright

Date: June 23, 2010

Porter Wright Morris & Arthur LLP Huntington Center 41 South High Street Columbus, OH 43215-6194Main Telephone #: 800-533-2794 Main Facsimile #: 614-227-2100

Client Matter #: 3994994 - 149832

Facsimile Cover Sheet

SENDER'S FACSIMILE RECEIVING #: 614-227-2100

IF YOU HAVE RECEIVED THIS COMMUNICATION IN ERROR OR IF YOU HAVE ANY PROBLEMS RECEIVING THIS COMMUNICATION, PLEASE CALL (513) 948-1500 IMMEDIATELY. THANK YOU.

THE INFORMATION CONTAINED IN THIS COMMUNICATION IS CONFIDENTIAL AND SUBJECT TO ATTORNEY CLIENT, WORK PRODUCT, OR OTHER LEGAL PRIVILEGE. THIS COMMUNICATION IS INTENDED CONLY FOR THE USE OF THE INDIVIDUAL OR EMITTY NAMED AS RECIPIENT, IF THE READER OF THIS COMMUNICATION IS NOT THE UNTENDED RECIPIENT, YOU ARE HEREBY NOTIFIED THAT ANY DISSEMINATION, DISTRIBUTION OR COPYING OF THIS COMMUNICATION IS STRICTLY PROHIBITED.

User: 6797

	TOTAL NUM	IBER OF PA	GES INCLUDING (COVER SHEET:	-	3		
	PLEASE DELIVER TO:							
	NAME FI		Firm		FACSIMILE #:		CONFIRMATION #.	
1.	RAM KACKAR	KACKAR USPTO		571-2	571-273-1436			
Со	mments:							
Fro	m: Melanie R. Ma ORIGINAL OF THIS D		WILL BE SENT BY:	Phone No	. 614-	227-2116		
	☐ ORDINARY MAIL		OVERNIGHT DELIVERY SERVICE					
	☐ MESSEN	GER -						

In re:

Serial Number:

10/800,553

Filed:

March 15, 2004

Attorney's Docket No.: 3994994-149832

TITLE: HOLDER FOR SAMPLE MATERIALS USED IN HIGH THROUGHPUT...

INVENTOR: HE, Ting et al.

Please revise the specification as follows:

[0021] Figure 6 shows a cross section of the holder detailing an individual mechanism in the overall array for securing an individual electrode in the holder assembly showing the configuration of the elements: face plate 71 and fastening screws 72 attaching to block or middle plate 46M and retainer or rear plate 73 with fastening screws 74. The substrate 46... is shown maintained in the opening 103 of the column 102a in the middle plate 102... which is concentrically aligned with opening 101... in the face plate. The spring 77 and electrode retainer 76 exert a force upon the electrode to secure the electrode at the spot area 80 at which the surface of the electrode is exposed to the plasma beam during the coating process. Small mask 75 in the opening 101... is at the base of a chamfer or bevel 71C in the opening 101... in faceplate 71. Thus the upper section of the electrode substrate 46... is inset into the face plate 71. A small oversize tolerance in the column 102... in middle plate 46M facilitates the insertion of the electrode. Large mask 90 overlays the face plate opening 101...

REPLACEMENT SHEET

TITLE: HOLDER FOR SAMPLE MATERIALS USED IN HIGH THROUGHPUT PHYSICAL VAPOR DEPOSITION MATERIAL STUDIES INVENTOR: HE, Ting et al.

CONTACT: EDWIN BARANOWSKI (614-227-2188)

